

SPEC DATA SHEET SQ-115

ANC-3010, ANC-3010B, ANC-3010T & ANC-3010BT

ceiling grid panel are offered as both a sound absorbing as well as a combination sound absorbing / sound blocking tile.

ANC-3010 ceiling grid panel have a white fabric facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

ANC-3010B ceiling grid panel take the standard C-300 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements



Substrate:	6-7# PCF rigid fiberglass core *C-300B adds a vinyl noise barrier	<ul style="list-style-type: none"> • Standard size 2' x 2' or 2' x 4' • Custom sizes available • Square or tegular edge • 1" or 2" thickness • Signature white fabric facing • Custom fabric facings available • Excellent acoustical values offered with a vinyl noise barrier for high STC requirements
Mounting:	Grid supplied by others	
Facing:	White or Black Poly Vinyl	
Edge Detail:	Square or regular	
Finish:	Signature white fabric facing Option for any Guilford of Maine FR701-2100 fabrics	

Acoustical NRC Rating:

1" Thick .85
2" Thick 1.15
C-100B Version STC 26

Weights	ANC-3010 Tile .6 lbs / SqFt ANC-3010B Tile 1.6 lbs / SqFt
Fire Rating:	All components have a Class A fire rating per ASTM E-84

Other Specifications:

Specifications can be downloaded from our website
www.soundseal.com or call us at 1.800.569.1294