

ACOUSTICAL PRODUCTS

ANC-3000 ACOUSTICAL WALL & CEILING PANELS

SPEC ANC-3000



Typically used as an economic Sound Curtain on temporary construction projects, offering a 3-5 year life span. The exterior grade VCP acing is specifically formulated for outdoor applications. Composite products offer maximum noise reduction by both blocking and absorbing noise at job sites. Also available with a two-pound psf barrier or a one-inch thick quilted fiberglass absorber.

- Low cost, economical baffles
- Excellent acoustical performance
- Stitched edges for extra durability
- Custom sizing • Easy to install
- Wide variety of finishes

The edges are available in natural or chemically hardened and are available in 4 edge profiles. S-2000 panels are available in standard or custom-sizes (up to a maximum of 5' X10') with custom, designer or C.O.M fabric available.

HIGH-QUALITY, ECONOMICAL, MULTI-PURPOSE PANELS

- Excellent acoustical performance
- Class A fire rated•Standard, designer or C.O.M fabric
- Various mounting options
- Custom sizes and shapes

The ANC-3000 Standard Wall Panel provides the ultimate in acoustical performance with excellent NRC ratings as high as 1.15.

They are available in four standard thicknesses: 1/2", 1", 1-1/2" and 2" with custom thickness available up to 4".

The S-2000 Panels are constructed with a 6-7# PCF rigid fiberglass absorber core.