

DATASHEETS

# Industrial & Commercial Noise Control Solution

YOUR SUCCESS IS OURS.


## ANC-AB12-HT HIGH TEMPERATURE NOISE BARRIER/SOUND ABSORBER COMPOSITE

The barrier septum configuration offers the benefits of both sound absorption and noise barriers. All Noise Control's ANC-AB12-HT consists of a non-reinforced 1lb psf loaded vinyl noise barrier sandwiched between two layers of vinyl-coated fiberglass-cloth faced 1" quilted fiberglass sound absorbers faced with a silicone coated-fiberglass cloth. Curtain panels are constructed with grommets across the top and Velcro along the vertical edges. Rolls are available 4' wide x 25' long and can be supplied with edges bound or unbound

- STC rating 29
- Rolls are available 4' wide x 25' long and can be supplied with edges bound or unbound
- Available colors: gray
- Class A (or 1) flammability rated per ASTM E84

## APPLICATIONS

Typical uses include curtain panels in acoustical curtain enclosures. Also used as separator walls or divider partitions between noise sources. Commonly used to line the perimeter walls of a building, or as a free hanging noise barrier/sound absorber wall. Silicone faced composites are used where the product will be subjected to high temperature sunlight, water or oil. Also used where UV resistance is required.



## PRODUCT DATA

Description	Silicone coated fiberglass cloth facing on 1" quilted fiberglass/ 1lb-psf non-reinforced loaded vinyl barrier/Vinyl coated fiberglass cloth faced 1" quilted fiberglass
Flammability	Class A: Flame Spread: 4.017 Smoke density: 19.209
Nominal thickness	2.08 "
Temperature range	-90° to +550° F
Standard panel width	48" wide
Roll length	25' long
Weight	1.5 lb psf