




ANC-AB22 (2lb 2") Noise Barrier Composite Absorber

The barrier septum configuration offers the benefits of sound absorption and noise barriers. A non-reinforced 2-lb psf loaded vinyl barrier is sandwiched between two layers of quilted fiberglass absorbers. Curtain panels are constructed with grommets across the top and hook and loop fasteners along the vertical edges. Rolls are available 4' wide up to 25' long and can be either bound or unbound.

- Class 1 or A per ASTM E84
- STC rating 33
- NRC rating 0.85
- Available colors: gray, white, black, or tan



Applications:

Typical uses include curtain material in acoustical curtain enclosures. Also used as separator walls or divider partitions. Commonly used to line the perimeter walls of a building.

Product Data

Description :

1" vinyl faced quilted fiberglass / 2LB-psf non-reinforced loaded vinyl barrier / 1" vinyl faced quilted fiberglass

Nominal thickness 2.15"
 Temperature range -20° to +180° F
 Standard width 48"
 Roll length 25'
 Density 2.5LB psf

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
ANC-AB22	19	22	28	40	56	61	38

ASTM E-90 & E 413

Product	OCTAVE BAND FREQUENCIES (Hz)						
	125	250	500	1000	2000	4000	NRC
ANC-AB22	.19	.99	.96	.80	.57	.33	.85

ASTM C 423