

SPEC DATA SHEET SQ-113

ANC-2100 & ANC-2100B ACOUSTICAL CEILING TILES

CEILING TILES



Substrate: 6-7# PCF rigid fiberglass core
*C-200B adds a vinyl noise barrier

Mounting: Grid supplied by others

Facing: White or Black Poly Vinyl

Edge Detail: Square

Finish: White nubby cloth facing

Acoustical NRC Rating:

1" Thick	.85
2" Thick	1.15
C-200B Version	STC 26

Weights: C-200 Tile .6 lbs / SqFt
C-200B Tile 1.6 lbs / SqFt

Fire Rating: All components have a Class A fire rating
per ASTM E-84

Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing / sound blocking tile.

ANC-2100 Ceiling Tiles have a white nubby cloth facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

ANC-200B Ceiling Tiles take the standard C-200 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- White nubby cloth facing
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements