

SPEC DATA SHEET SQ-115

ANC-3010, ANC-3010B, ANC-3010T & ANC-3010BT

ACOUSTICAL CEILING TILES



Substrate: 6-7# PCF rigid fiberglass core
*C-300B adds a vinyl noise barrier

Mounting: Grid supplied by others

Facing: White or Black Poly Vinyl

Edge Detail: Square or regular

Finish: Signature white fabric facing
Option for any Guilford of Maine FR701-2100 fabrics

Acoustical NRC Rating:

1" Thick	.85
2" Thick	1.15
C-300B Version	STC 26

Weights: ANC-3010 Tile .6 lbs / SqFt
ANC-3010B Tile 1.6 lbs / SqFt

Fire Rating: All components have a Class A fire rating per ASTM E-84

Other Specifications:
Specifications can be downloaded from our website
www.soundseal.com or call us at 1.800.569.1294

Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing / sound blocking tile.

ANC-3010 Ceiling Tiles have a white fabric facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

ANC-3010B Ceiling Tiles take the standard C-300 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- Square or tegular edge
- 1" or 2" thickness
- Signature white fabric facing
- Custom fabric facings available
- Excellent acoustical values offered with a vinyl noise barrier for high STC requirements