

SPEC DATA SHEET SQ-112

# ANC-1010 - 1010B

ACOUSTICAL CEILING TILES



Substrate: 6-7# PCF rigid fiberglass core  
\*C-100B adds a vinyl noise barrier

Mounting: Grid supplied by others

Edge Detail: Square

Finish: 2 mil white pebble grain vinyl

Acoustical NRC Rating:  
1" Thick .85  
2" Thick 1.15  
C-100B Version STC 26

Weights: C-100 Tile .6 lbs / SqFt C-100B  
Tile 1.6 lbs / SqFt

Ceiling tiles are offered as both a sound absorbing as well as a combination sound absorbing / sound blocking tile.

Ceiling Tiles have a 2 mil white pebble grain vinyl facing attached to a 1" or 2" thick rigid fiberglass board and have excellent sound absorption (NRC) ratings.

Ceiling Tiles take the standard ANCC-1010 tile and add a 1# per square foot foil backed vinyl noise to the backside of the tile for high sound absorption (NRC) and high sound blocking (STC) requirements.

- Standard size 2' x 2' or 2' x 4'
- Custom sizes available
- 1" or 2" thickness
- 2 mil white pebble grain finish
- Excellent acoustical values
- Offered with a vinyl noise barrier for high STC requirements