

WALL PANEL KITS

ANC-3000 Acoustical Wall Panel Kits

The ANC-PK3000 is customizable partition kits for use with our standard absorber panel that is perfect for most applications with the exception of use in high abuse areas, ANC-3000.

Call us to discuss your needs and we will share essentially the unlimited options that ANC-3000 wall panel and its ANCPK3000 partition kits can be configured to solve your office acoustic needs.

Below are our ANC-3000 Specs & Acoustical data for your convenience.

ANC-3000 ACOUSTIC WALL PANEL DETAILS:

WALL PANEL SUBSTRATE

6-7# PCF rigid fiberglass core with optional chemically hardened edges



WALL PANEL MOUNTING

Impaling clips, 2 part mechanical clips, Hook & Loop fasteners, construction adhesive.



WALL PANEL FINISHES

Guilford of Maine FR 701 Style 2100 is standard . Designer and customer specified fabrics are available

ACOUSTICAL WALL PANEL NRC RATINGS

1/2" :	.50 - .60
1" :	.80 - .90
2" :	1.05 - 1.15

WALL PANEL EDGE DETAILS

Square, Bevel, Radius, Miter

ANC-3000 WALL PANEL INSTALLATION INSTRUCTIONS

The ANC-3000 panel can be installed on walls or ceiling using mechanical clips, adhesive or hook & loop.

Consult with factory for best-suited mounting for your application.

PHYSICAL PROPERTIES

- Colors : 48 polyester fabric Guilford colors
- Size: Custom cut thru 4'x 10'
- Thickness: 1/2", 3/4", 1", 1 1/2 & 2"
- Density: 7 pounds per cubic foot
- Fire Rating : ASTM E 84 Class A approved
- Smoke Density: 22.75
- Breaking Strength: 150 lb/in.
- Density: 2 lb/ft
- Temperature Limits: -20OF to 180OF



FREQUENCY(Hz)	125	250	500	1K	2K	4K	NRC
1" Thick	.11	.30	.77	1.02	1.00	1.00	.85
2" Thick	.46	1.00	1.07	1.05	1.10	1.18	1.15