

Clear Vinyl Noise Barrier

Clear Vinyl is a transparent poly-vinyl chloride noise, wind and thermal barrier. It is designed to minimize the passage of sound, heat, cold, or wind from one area to another while offering maximum visibility. ANC-VB-60 is also available in a USDA approved version.



- Rolls are available 48" wide up to 60'
- Strips are available 16" wide up to 100' long
- Offers significant noise reduction while allowing for visibility and easy access

Applications:

Clear Vinyl is available in roll form (up to 60' long), or in fabricated panels with grommets at the top and Velcro seals along each vertical edge. Standard panel width is 48", length as required. Custom sizes are available. In strip form rolls are available up to 100' long. Strips cut to length are available with mounting holes punched 2" on center.

Product Data:

Description	1LB-psf transparent PVC barrier
Standard width	48" sheet/roll, 16" strips
Temperature range	0° F to +150° F
Thickness	.160 inches
Thermal Conductivity	0.73 Btu/(hr)(sq.ft.)(deg. F/in)

Acoustical Performance:

Sound Transmission Loss (dB)

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
Clear Vinyl	13	17	22	26	32	37	26

ASTM E-90