

SPEC DATA SHEET


# ANC-WB42 WRAP BARRIER 2" Decoupler

## PIPE AND DUCT WRAP

### ACOUSTICAL PIPE AND DUCT LAGGING: ANC-WB42 WRAP BARRIER 2" DECOUPLER

A composite material featuring a flexible one-pound per square foot reinforced-foil faced loaded vinyl noise barrier bonded to a 2" thick scrim faced quilted sound absorber/decoupler. Used to wrap noisy pipes, ducts, valves and fan housings.

- Standard roll is 54" wide x 30' long
- Accepts matching Wrap Tape for easy Installation
- Class A (or 1) flammability rating per ASTM E-84



### APPLICATIONS

Typically used to wrap noisy pipes and ducts to block the noise that transmits through the walls of the pipe or duct as air or other contents move through it. The 2" thick quilted fiberglass absorber/decoupler improves low frequency acoustical performance, overall performance of the noise barrier, and provides sound absorption and thermal insulation around the pipe or ductwork. The reinforced foil facing on the barrier readily accepts a matching lag tape for easy installation.

### PRODUCT DATA

Description	1 Lb-psf foil-faced loaded vinyl barrier bonded to a 2" thick scrim faced quilted fiberglass absorber		
Nominal thickness	2.0 inches		
Standard width	54" wide		
Roll length	30 feet		
Weight	1.3 LB psf		
"R" Factor	9.0		
Flammability	Smoke Density index	19.5	
	Flame spread index	12.5	
Temperature range	-20° to +200° F		

### ACOUSTICAL DATA

#### Sound transmission Data

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
<b>ANC-WB42/ 2" Decouper</b>	19	20	23	33	44	53	30

Per ASTM E-90