

Acoustical Room Kit 10 consist of select Broadway panels and mounting hardware. Acoustic panels are constructed of high density (6lbs/pcf) rigid glass wool with resin hardened edges. The edge treatment works in tandem with the micro-mesh to fully encapsulate and contain the glass fibers. The outer fabric covering is acoustically transparent polyester and available in three neutral colors for an architecturally attractive appearance.

Installation is easy with the included mounting hardware. We even supply the screws, drywall anchors and drill bit to get you started fast.

Broadway panels have been tested to meet stringent Class-A/1 fire ratings making them suitable for use in residential and commercial spaces.

| | |
|-----------------------------|----------------------------------------------------------|
| Core Material | Formed, semi rigid inorganic glass fibers |
| Density | 6.0 lbs. per cubic foot (96 kg/m ³) |
| Fabric Facing | Acoustically transparent polyester tweed |
| Encapsulation | Micromesh on front and rear surface, resin treated edges |
| Absorption H ₂ O | < 2% by weight @ 120°F (49°C), 95% relative humidity |
| Temperature | -20°F ~ 150°F (-29°C ~ 66°C) |
| Fire Rating | Class-A/1 (ASTM E 84 / CAN/UL-S102) |
| Mounting | Galvanized steel impalers, drywall anchors and screws |



LEED certification provides independent, third-party verification that a building, home or community was designed and built using strategies aimed at achieving high performance in key areas of human and environmental health.