

ANC-AB220 QUILTED FIBERGLASS ABSORBER

All Noise Control Exterior Grade Quilted Fiberglass Absorbers reduce the reflection of sound waves by covering reflective surfaces with a suitably protected porous, open-celled material. ANC-AB220 consists of an exterior grade, UV resistant heavy-duty VCP facing on both sides of a 1" thick quilted fiberglass. Modular panels are constructed with grommets across the top and bottom and are sewn with Gore Tenara exterior grade thread. The product is also available in roll form with edges bound or unbound.

FEATURES

- Superior UV and weather resistance
- Available facing colors on quilt: gray, tan, black, off-white
- NRC rating 0.65

APPLICATIONS:

Exterior Grade faced quilted fiberglass absorbers are used to reduce reverberant noise on permanent outdoor applications such as enclosing HVAC equipment, dust collectors or similar machinery behind a manufacturing plant where UV resistance is required. It is commonly installed over wood fencing or on brick or masonry walls of buildings adjacent to a job site or a noisy piece of machinery.



PRODUCT DATA:

DESCRIPTION:

Vinyl Coated Polyester (VCP)
facing / 1" fiberglass batt
Vinyl Coated Polyester (VCP)
facing

FLAMMABILITY:

Flame Spread: 23.0
Smoke density: 30.0

NOMINAL THICKNESS:

1.0 inches

TEMPERATURE RANGE:

-40° to +180° F

STANDARD ROLL SIZE:

48" wide-25' long

WEIGHT:

0.35 lb psf

ACOUSTICAL PERFORMANCE:

SOUND TRANSMISSION LOSS

PRODUCT	OCTAVE BAND FREQUENCIES (HZ)						NRC
	125	250	500	1000	2000	4000	
ANC-AB220	.18	.69	.74	.72	.42	.29	.85

ASTM C 423

Address: 2731 Vista Parkway # D-6 WPB, Florida 33411

Phone: 561-964-9360

Email: info@allnoisecontrol.com