

ANC-700 BANNER SPECIFICATION

MODEL ANC-700

PART I - GENERAL

1.1 Work Included:

The work consists of furnishing all labor, materials, accessories and equipment necessary to cover all areas shown on the drawings and specified herein with ANC Panels.

1.2 Delivery and Storage:

Store this product in unopened cartons in a clean, cool, dry interior space. Cartons and product must be protected against marring, water, dirt or damage during delivery and storage.

PART II: PRODUCT

- 2.1.1 Geometric Shape:** Rectangular
- 2.1.2 Size & Thickness:** (2" thick) (4' x 2')
- 2.1.3 Core:** 3/4# fiberglass
- 2.1.4 Surface Finish:**
(PVC perforated one side) (nylon sailcloth perforated one side) (also available solid both sides for high humidity environments)
- 2.1.5 Color:**
To be selected by architect from manufacturer's standard selection

PART III: EXECUTION

3.1 Installation

3.1.1 ANC acoustical panels shall be located and spaced as detailed on reflected ceiling plans and/or detailed on the interior elevation drawings and as indicated on room finish schedule

3.1.2 Suspend Panels From:

(existing construction) (cable) (fasteners [type])

3.1.3 Attachment Method:

(heavy duty plastic tie) (coated wire tie)
(beam clamps) (cable)

3.1.4 Workmanship:

The acoustical system shall be installed only by an approved contractor.

All work shall be completed in a workman like manner. All panels shall be properly installed and left in a clean, sanitary condition. Contractor shall remove and dispose of shipping containers and debris.

2.1.6 Edge Shape:	Natural
2.1.7 Edge Construction:	(Heat sealed)
2.1.8 Acoustical Performance:	1.0 N.R.C.
2.1.9 Incombustability:	Class "A"
2.1.10 Suspension Provision:	(Grommets)