



BANNERS (BN)

PRODUCT FEATURES

- Economical sound absorption
- Excellent sound absorption
- Flexible and adjustable
- Great design potential
- Adds design and color to ceilings
- Popular in large venues, arenas, stadiums, and cafeterias

CORE

75-1.65 pcf fiberglass
2" and 4" thick

SIZES

Up to 4' x 25'
Intermediate support suggested
for Banners over 10' long

MOUNTING

Washers or stiffeners

EDGES

Natural

FINISH

Nylon and PVC (with or without
perforated sides)

FLAMMABILITY

All components have a Class "A"
rating per ASTM E84

SOUND ABSORPTION

– BN2PP: 2", PVC, PERFORATED, 1.2 PCF

HZ	125	250	500	1000	2000	4000	NRC
BN2PP	.90	1.06	1.02	1.10	1.15	1.22	1.10

– BN2PS: 2", PVC, SOLID, 1.2 PCF

HZ	125	250	500	1000	2000	4000	NRC
BN2PS	.85	1.04	1.03	1.06	.69	.42	.95

– BN2N: 2", NYLON, 1.65 PCF

HZ	125	250	500	1000	2000	4000	NRC
BN2N	.83	1.02	1.00	1.04	.64	.39	.95

– BN4PP: 4", PVC, PERFORATED, 1.65 PCF

HZ	125	250	500	1000	2000	4000	NRC
BN4PP	1.31	1.11	1.14	1.17	1.15	1.19	1.15

For best sound absorption, perforated sides should be installed
facing the floor.