



ACOUSTICAL CEILING PANELS (ACP)

PRODUCT FEATURES

- Fabric finish
- Durable, high-sound absorption
- Variety of mounting options
- Custom sizes and shapes
- Attached to metal deck in open ceiling designs
- Typical applications: band rooms, auditoriums and churches.

SOUND ABSORPTION – Direct Mount

Hz	125	250	500	1000	2000	4000	NRC
ACP 1	.10	.25	.84	1.08	1.13	1.11	.85
ACP 1.5	.31	.58	1.03	1.10	1.05	1.04	.95
ACP 2	.42	.89	1.12	1.07	1.10	1.09	1.05

SOUND ABSORPTION – Lay-In Ceiling

Hz	125	250	500	1000	2000	4000	NRC
ACP 1	.94	1.00	.80	1.05	1.07	1.15	1.00

Note: NRC test results based on our standard acoustically transparent fabric. Results may vary with other fabrics.

CORE

6 – 7 pcf fiberglass
1" – 2" thick

SIZES

Direct Mount: up to 4' x 8'
Lay-In: up to 5' x 5'

MOUNTING

Lay-in grid, continuous hanger bar, pucks

EDGES

Square, bevel, micro-bevel (for adjoined panels), radiused. Hardened if required

FINISH

Fabric finish

FLAMMABILITY

All components have a Class "A" rating per ASTM E84