

All Noise Control offers one, two, and three-story inplant offices that can meet any space requirement. Available with a range of core materials and surface finishes, these versatile structures are built in a fraction of the time and cost compared to traditional "stick-built" construction. Each unit comes with a detailed installation manual and drawings for easy assembly.



Modular Inplants



Features

- Reusable, re-locatable, and expandable design
- Easy installation with minimal facility disruption
- Load bearing storage roofs available
- Variety of colors and finishes
- Multi-story options optimize space and value
- Solid construction withstands manufacturing and military environments



Standard Options

- Three inch insulated wall panels in choice of white, gray, and champagne
- 22 gauge galvanized top decking and suspended acoustical ceiling
- Framing and all connecting hardware always included
- 3-0 x 7-0 20 gauge steel with 20" x 30" window and hardware
- Electric package includes junction boxes, breaker panel, light switch, duplex outlets, and 2' x 4' fluorescent fixtures



Applications

- Inplant Office
- Conference Room
- Breakroom
- Machine Enclosure
- Cleanrooms
- Shipping Office
- Paint Booth

WALL PANEL OPTIONS

Wall	Interior & exterior use	Benefits
G/G	4-mil vinyl laminated to 1/2" type X fire rated Gypsum (x2)	Price efficient. Good for insulation. Plus sound and fire resistance
GB/ BG	5/8" Vinyl Covered Gypsum (x2), 1/8" SoundStop Board 1/2" gypsum (x2)	Same as above with increased rigidity and sound proofing
G/G Ballistic	Ballistic fiberglass (thickness varies based upon ballistic rating level)	Great for office space in high risk environments
S/S	26 gauge stucco-embossed steel (x2)	Highly durable. Handles harsh conditions and easily cleaned
S/G	1/2" Vinyl Covered Gypsum 26 guard stucco-embossed steel to 1/8" hard board (x2)	Durable exterior for offices placed in harsh environments
SB/BS	26 gauge stucco-embossed steel to 1/2" gypsum board (x2)	Our strongest steel panel, holds up against the worst environments
SG/GS	26 gauge stucco-embossed steel to 1/2" gypsum board (x2)	Durable with great insulation and sound resistance
SG/GS Non-Combustible	2" mineral wool core 26 gauge stucco embossed steel to 5/8" gypsum panel 2" mineral wool core	Same as above with increased fire protection
1 HR Fire Rated	26 gauge stucco embossed steel .090 stucco embossed fiberglass reinforced plastic	Able to withstand an open flame for up to an hour while hold its structural integrity
S/FRP	.090 stucco embossed fiberglass reinforced plastic (x2) .090 stucco embossed fiberglass reinforced plastic to 1/8" hardboard (x2)	Durable exterior and easily cleaned inside and out. Great for exterior bathrooms Impact/scratch resistant, easy to clean, USDA approved and does not support mold or mildew growth
FRP/FRP	.090 stucco embossed fiberglass reinforced plastic 1/2" vinyl covered gypsum board	Same as above. More rigidity and soundproofing
FRP-B/B-FRP		
FRP/G		Great for an internal bathroom area that shares a wall with an office area.

*All panels mentioned above come equipped with either polystyrene or poly-iso cores, unless noted otherwise.

Say goodbye to painting with our commercial-grade vinyl-coated gypsum wall panels. Built to provide excellent fire and sound control, these 3" thick walls are perfect for offices in light-duty warehouse or moderate industrial environments. All Noise Control's high-performance modular wall panels feature premium facings, ensuring a 3" wall thickness that excels in structural strength, fire resistance, sound insulation, thermal performance, impact resistance, and overall durability.

COLOR OPTIONS

Vinyl Options



White

Dove Gray


Steel Options



White

Saddle Tan


Gray



G/G



S/S



FRP/FRP