

Window Options



Binder Post System

Our binder post system offers a strong and stable connection between wall panels and windows. It is available with 1/8", 1/4", and 1/2" tempered glass options. The glass thickness for each project depends on the specific requirements. For a lower U-Value, an insulated option is available for both interior and exterior buildings. Standard picture windows are typically 3'8" wide by 3' high.



Divider Strip System

PBI's exclusive divider strip connection system delivers a traditional appearance while preserving the benefits of modular construction. With this system, the window is directly installed into the panel. Similar to our Binder Post System, these windows are available in 1/8", 1/4", and 1/2" thicknesses, depending on the project requirements. Standard picture windows are typically 3'8" wide by 3' high.



Slider Window

All Noise Control's slider window option is primarily used in guard booths but can also be adapted for interior office settings. Like our other window options, these can be insulated to achieve a lower U-value. Our standard slider window features 1/4" tempered glass with an aluminum finish. Horizontal sliding windows are typically 3' wide by 3' high.



Fire Rated Wire Glass

Tested for 45 minutes of fire exposure, reaching temperatures up to 1600°F, followed by being sprayed with a stream of water at a pressure of 30 psi, the glass breaks but remains in place, qualifying it as fire-resistant under these conditions. The glass is 3/16" thick, with mesh embedded inside. The 45-minute rated picture windows are typically 3' wide by 3' high.
